

Metallized Polyester (PET) Capacitors PCM 7.5 mm to 37.5 mm

Special Features

- High volume/capacitance ratio
- Self-healing
- According to RoHS 2002/95/EC

Typical Applications

For general DC-applications e.g.

- By-pass
- Blocking
- Coupling and decoupling
- Timing

Construction


Dielectric:

Polyethylene-terephthalate (PET) film

Capacitor electrodes:

Vacuum-deposited

Internal construction:



Encapsulation:

Solvent-resistant, flame-retardant plastic case with epoxy resin seal, UL 94 V-0

Terminations:

Tinned wire.

Marking:

Colour: Red. Marking: Black.
Epoxy resin seal: Red

Electrical Data

Capacitance range:

1000 pF to 220 μ F (E12-values on request)

Rated voltages:

50 VDC, 63 VDC, 100 VDC, 250 VDC, 400 VDC, 630 VDC, 1000 VDC, 1500 VDC, 2000 VDC

Capacitance tolerances:

$\pm 20\%$, $\pm 10\%$ $\pm 5\%$

Operating temperature range:

-55° C to $+100^{\circ}$ C

Climatic test category:

55/100/56 in accordance with IEC

Insulation resistance at $+20^{\circ}$ C:

U_r	U_{test}	$C \leq 0.33 \mu F$	$0.33 \mu F < C \leq 220 \mu F$
50 VDC	10V	$\geq 5 \times 10^3 M\Omega$ (mean value: $3 \times 10^4 M\Omega$)	$\geq 1500 \text{ sec} (M\Omega \times \mu F)$ (mean value: 4500 sec)
63 VDC	50V	$\geq 1 \times 10^4 M\Omega$ (mean value: $5 \times 10^4 M\Omega$)	$\geq 3000 \text{ sec} (M\Omega \times \mu F)$ (mean value: 6000 sec)
100 VDC	100V	$\geq 1.5 \times 10^4 M\Omega$ (mean value: $5 \times 10^4 M\Omega$)	$\geq 5000 \text{ sec} (M\Omega \times \mu F)$ (mean value: 15000 sec)
≥ 250 VDC	100V	$\geq 3 \times 10^4 M\Omega$ (mean value: $1 \times 10^5 M\Omega$)	$\geq 10000 \text{ sec} (M\Omega \times \mu F)$ (mean value: 40000 sec)

Measuring time: 1 min.

Dissipation factors at $+20^{\circ}$ C: $\tan \delta$

at f	$C \leq 0.1 \mu F$	$0.1 \mu F < C \leq 1.0 \mu F$	$C > 1.0 \mu F$
1 kHz	$\leq 8 \times 10^{-3}$	$\leq 8 \times 10^{-3}$	$\leq 10 \times 10^{-3}$
10 kHz	$\leq 15 \times 10^{-3}$	$\leq 15 \times 10^{-3}$	-
100 kHz	$\leq 30 \times 10^{-3}$	-	-

Maximum pulse rise time:

Capacitance pF/ μ F	Pulse rise time V/ μ sec max. operation/test								
	50VDC	63VDC	100VDC	250VDC	400VDC	630VDC	1000VDC	1500VDC	2000VDC
1000 ... 6800	-	-	-	-	-	-	70/700	90/900	100/1000
0.01 ... 0.022	-	30/300	30/300	35/350	38/380	40/400	50/500	50/500	60/600
0.033 ... 0.068	-	15/150	15/150	20/200	25/250	32/320	26/260	35/350	40/400
0.1 ... 0.22	10/100	10/100	12/120	15/150	15/150	17/170	20/200	35/350	40/400
0.33 ... 0.68	9/90	9/90	9/90	10/100	10/100	13/130	20/200	20/200	38/380
1.0 ... 2.2	6/60	6/60	5/50	6/60	9/90	13/130	14/140	15/150	-
3.3 ... 6.8	2.5/25	3/30	3/30	6/60	6/60	9/90	12/120	-	-
10 ... 220	2.5/25	2.5/25	2.5/25	3/30	6/60	-	-	-	-

for pulses equal to the rated voltage

Mechanical Tests

Pull test on leads:

$d \leq 0.8 \phi$: 10 N in direction of leads
 $d > 0.8 \phi$: 20 N in direction of leads
according to IEC 60068-2-21

Vibration:

6 hours at 10...2000 Hz and 0.75 mm displacement amplitude or 10 g in accordance with IEC 60068-2-6

Low air density:

1kPa = 10 mbar in accordance with IEC 60068-2-13

Bump test: 4000 bumps at 390 m/sec² in accordance with IEC 60068-2-29

Packing

Available taped and reeled up to and including case size 15 x 26 x 31.5 / PCM 27.5 mm.

Detailed taping information and graphs at the end of the catalogue.

For further details and graphs please refer to Technical Information.

Continuation

General Data


Capacitance	50 VDC/30 VAC*					63 VDC/40 VAC*				
	W	H	L	PCM**	Part number	W	H	L	PCM**	Part number
0.01 μF						2.5	7	10	7.5	MKS4C021002A00_____
0.015 "						4	9	13	10	MKS4C021003C00_____
0.022 "						2.5	7	10	7.5	MKS4C021502A00_____
0.033 "						4	9	13	10	MKS4C021503C00_____
0.047 "						2.5	7	10	7.5	MKS4C022202A00_____
0.068 "						4	9	13	10	MKS4C022203C00_____
						2.5	7	10	7.5	MKS4C023302A00_____
						4	9	13	10	MKS4C023303C00_____
						2.5	7	10	7.5	MKS4C024702A00_____
						4	9	13	10	MKS4C024703C00_____
						2.5	7	10	7.5	MKS4C026802A00_____
						4	9	13	10	MKS4C026803C00_____
0.1 μF	2.5	7	10	7.5	MKS4B031002A00_____	2.5	7	10	7.5	MKS4C031002A00_____
0.15 "	2.5	7	10	7.5	MKS4B031502A00_____	4	9	13	10	MKS4C031003C00_____
0.22 "	2.5	7	10	7.5	MKS4B032202A00_____	2.5	7	10	7.5	MKS4C031502A00_____
0.33 "	2.5	7	10	7.5	MKS4B033302A00_____	4	9	13	10	MKS4C031503C00_____
0.47 "	3	8.5	10	7.5	MKS4B034702B00_____	3	8.5	10	7.5	MKS4C032202B00_____
0.68 "	4	9	10	7.5	MKS4B036802C00_____	4	9	13	10	MKS4C032203C00_____
						4	9	10	7.5	MKS4C033302C00_____
						4	9	13	10	MKS4C033303C00_____
						4	9	10	7.5	MKS4C034702C00_____
						4	9	13	10	MKS4C034703C00_____
						5	10.5	10.3	7.5	MKS4C036802E00_____
						4	9	13	10	MKS4C036803C00_____
1.0 μF	4	9	10	7.5	MKS4B041002C00_____	5	10.5	10.3	7.5	MKS4C041002E00_____
1.5 "	5	10.5	10.3	7.5	MKS4B041502E00_____	4	9	13	10	MKS4C041003C00_____
2.2 "	5.7	12.5	10.3	7.5	MKS4B042202F00_____	5.7	12.5	10.3	7.5	MKS4C041502F00_____
3.3 "	5.7	12.5	10.3	7.5	MKS4B043302F00_____	5	11	13	10	MKS4C041503F00_____
4.7 "	7.2	12.5	10.3	7.5	MKS4B044702G00_____	5	11	13	10	MKS4C042203F00_____
6.8 "	6	12	13	10	MKS4B044703G00_____	6	12.5	18	15	MKS4C042204C00_____
	7.2	12.5	10.3	7.5	MKS4B046802G00_____	6	12	13	10	MKS4C043303G00_____
	6	12	13	10	MKS4B046803G00_____	7	14	18	15	MKS4C043304D00_____
						7	14	18	15	MKS4C044704D00_____
						6	15	26.5	22.5	MKS4C044705B00_____
						8	15	18	15	MKS4C046804F00_____
						7	16.5	26.5	22.5	MKS4C046805D00_____
10 μF	9	16	18	15	MKS4B051004J00_____	8.5	18.5	26.5	22.5	MKS4C051005F00_____
15 "	11	21	26.5	22.5	MKS4B051505I00_____	11	21	31.5	27.5	MKS4C051006B00_____
22 "	11	21	31.5	27.5	MKS4B052206B00_____	11	21	26.5	22.5	MKS4C051505I00_____
33 "	13	24	31.5	27.5	MKS4B053306D00_____	11	21	31.5	27.5	MKS4C051506B00_____
47 "	15	26	31.5	27.5	MKS4B054706F00_____	13	24	31.5	27.5	MKS4C052206D00_____
68 "	13	24	41.5	37.5	MKS4B054707C00_____	15	26	31.5	27.5	MKS4C053306F00_____
	20	39.5	31.5	27.5	MKS4B056806J00_____	17	29	31.5	27.5	MKS4C054706G00_____
	17	29	41.5	37.5	MKS4B056807E00_____	17	29	41.5	37.5	MKS4C054707E00_____
						20	39.5	31.5	27.5	MKS4C056806J00_____
						19	32	41.5	37.5	MKS4C056807F00_____
100 μF	19	32	41.5	37.5	MKS4B061007F00_____	20	39.5	41.5	37.5	MKS4C061007G00_____
150 "	20	39.5	41.5	37.5	MKS4B061507G00_____	24	45.5	41.5	37.5	MKS4C061507H00_____
220 "	24	45.5	41.5	37.5	MKS4B062207H00_____					

* AC voltage: $f = 50 \text{ Hz}$; $1.4 \times U_{\text{rms}} + \text{UDC} \leq U_r$

**PCM = Printed circuit module
= lead spacing

Dims. in mm.

$\varnothing d$	PCM	W
0.5	7.5	≤ 3
0.6	7.5	≥ 4
0.6	10	
0.8	15 - 27.5	
1.0	37.5	



Part number completion:	
Tolerance:	20 % = M
	10 % = K
	5 % = J
Packing:	bulk = S
Lead length:	6-2 = SD
Taped version see page 140.	

Rights reserved to amend design data without prior notification.

Continuation

General Data

Capacitance	100 VDC/63 VAC*					250 VDC/160 VAC*				
	W	H	L	PCM**	Part number	W	H	L	PCM**	Part number
0.01 μ F	2.5	7	10	7.5	MKS4D021002A00_	3	8.5	10	7.5	MKS4F021002B00_
	4	9	13	10	MKS4D021003C00_	4	9	13	10	MKS4F021003C00_
0.015 "	2.5	7	10	7.5	MKS4D021502A00_	3	8.5	10	7.5	MKS4F021502B00_
	4	9	13	10	MKS4D021503C00_	4	9	13	10	MKS4F021503C00_
0.022 "	2.5	7	10	7.5	MKS4D022202A00_	3	8.5	10	7.5	MKS4F022202B00_
	4	9	13	10	MKS4D022203C00_	4	9	13	10	MKS4F022203C00_
0.033 "	2.5	7	10	7.5	MKS4D023302A00_	3	8.5	10	7.5	MKS4F023302B00_
	4	9	13	10	MKS4D023303C00_	4	9	13	10	MKS4F023303C00_
0.047 "	2.5	7	10	7.5	MKS4D024702A00_	3	8.5	10	7.5	MKS4F024702B00_
	4	9	13	10	MKS4D024703C00_	4	9	13	10	MKS4F024703C00_
0.068 "	2.5	7	10	7.5	MKS4D026802A00_	4	9	10	7.5	MKS4F026802C00_
	4	9	13	10	MKS4D026803C00_	4	9	13	10	MKS4F026803C00_
0.1 μ F	2.5	7	10	7.5	MKS4D031002A00_	4	9	10	7.5	MKS4F031002C00_
	4	9	13	10	MKS4D031003C00_	4	9	13	10	MKS4F031003C00_
0.15 "	3	8.5	10	7.5	MKS4D031502B00_	5	10.5	10.3	7.5	MKS4F031502E00_
	4	9	13	10	MKS4D031503C00_	4	9	13	10	MKS4F031503C00_
0.22 "	3	8.5	10	7.5	MKS4D032202B00_	5	10.5	10.3	7.5	MKS4F032202E00_
	4	9	13	10	MKS4D032203C00_	5	11	13	10	MKS4F032203F00_
0.33 "	4	9	10	7.5	MKS4D033302C00_	5.7	12.5	10.3	7.5	MKS4F033302F00_
	4	9	13	10	MKS4D033303C00_	5	11	13	10	MKS4F033303F00_
0.47 "	4.5	9.5	10.3	7.5	MKS4D034702D00_	6	12	13	10	MKS4F034703G00_
	4	9	13	10	MKS4D034703C00_	6	12.5	18	15	MKS4F034704C00_
0.68 "	5	10.5	10.3	7.5	MKS4D036802E00_	7	14	18	15	MKS4F036804D00_
	4	9	13	10	MKS4D036803C00_					
1.0 μ F	5.7	12.5	10.3	7.5	MKS4D041002F00_	8	15	18	15	MKS4F041004F00_
	5	11	13	10	MKS4D041003F00_	6	15	26.5	22.5	MKS4F041005B00_
1.5 "	6	12	13	10	MKS4D041503G00_	9	16	18	15	MKS4F041504J00_
	7	14	18	15	MKS4D041504D00_	7	16.5	26.5	22.5	MKS4F041505D00_
2.2 "	8	15	18	15	MKS4D042204F00_	10.5	19	26.5	22.5	MKS4F042205G00_
	6	15	26.5	22.5	MKS4D042205B00_	9	19	31.5	27.5	MKS4F042206A00_
3.3 "	9	16	18	15	MKS4D043304J00_	11	21	26.5	22.5	MKS4F043305I00_
	7	16.5	26.5	22.5	MKS4D043305D00_	11	21	31.5	27.5	MKS4F043306B00_
4.7 "	10.5	19	26.5	22.5	MKS4D044705G00_	11	21	31.5	27.5	MKS4F044706B00_
	9	19	31.5	27.5	MKS4D044706A00_					
6.8 "	10.5	19	26.5	22.5	MKS4D046805G00_	13	24	31.5	27.5	MKS4F046806D00_
	11	21	31.5	27.5	MKS4D046806B00_					
10 μ F	13	24	31.5	27.5	MKS4D051006D00_	17	29	31.5	27.5	MKS4F051006G00_
	13	24	31.5	27.5	MKS4D051506D00_	17	34.5	31.5	27.5	MKS4F051506I00_
22 "	15	26	31.5	27.5	MKS4D052206F00_	17	29	41.5	37.5	MKS4F051507E00_
	17	29	31.5	27.5	MKS4D053306G00_	19	32	41.5	37.5	MKS4F052207F00_
33 "	13	24	41.5	37.5	MKS4D053307C00_	24	45.5	41.5	37.5	MKS4F053307H00_
	17	29	41.5	37.5	MKS4D054707E00_					
47 "	17	29	41.5	37.5	MKS4D054707E00_					
	20	39.5	41.5	37.5	MKS4D056807G00_					
100 μ F	24	45.5	41.5	37.5	MKS4D061007H00_					

* AC voltage: $f = 50 \text{ Hz}$; $1.4 \times U_{\text{rms}} + U_{\text{DC}} \leq U_r$

**PCM = Printed circuit module = lead spacing

Dims. in mm.

Part number completion:

Tolerance: 20 % = M

10 % = K

5 % = J

Packing: bulk = S

Lead length: 6-2 = SD

Taped version see page 140.

Rights reserved to amend design data without prior notification.

Continuation page 60

Continuation

General Data

Capacitance	400 VDC/200 VAC*					630 VDC/400 VAC*				
	W	H	L	PCM**	Part number	W	H	L	PCM**	Part number
0.01 μF	3	8.5	10	7.5	MKS4G021002B00_	3	8.5	10	7.5*	MKS4J021002B00_
	4	9	13	10	MKS4G021003C00_	4	9	13	10	MKS4J021003C00_
0.015 "	3	8.5	10	7.5	MKS4G021502B00_	4	9	10	7.5*	MKS4J021502C00_
	4	9	13	10	MKS4G021503C00_	4	9	13	10	MKS4J021503C00_
0.022 "	4	9	10	7.5	MKS4G022202C00_	4.5	9.5	10.3	7.5*	MKS4J022202D00_
	4	9	13	10	MKS4G022203C00_	4	9	13	10	MKS4J022203C00_
0.033 "	4	9	10	7.5	MKS4G023302C00_	5	10.5	10.3	7.5*	MKS4J023302E00_
	4	9	13	10	MKS4G023303C00_	5	11	13	10	MKS4J023303F00_
0.047 "	5	10.5	10.3	7.5	MKS4G024702E00_	5.7	12.5	10.3	7.5*	MKS4J024702F00_
	4	9	13	10	MKS4G024703C00_	6	12	13	10	MKS4J024703G00_
0.068 "	5	10.5	10.3	7.5	MKS4G026802E00_	6	12	13	10	MKS4J026803G00_
	4	9	13	10	MKS4G026803C00_	5	11	18	15	MKS4J026804B00_
0.1 μF	5	10.5	10.3	7.5	MKS4G031002E00_	6	12.5	18	15	MKS4J031004C00_
	5	11	13	10	MKS4G031003F00_	6	15	26.5	22.5	MKS4J031005B00_
0.15 "	5.7	12.5	10.3	7.5	MKS4G031502F00_	7	14	18	15	MKS4J031504D00_
	6	12	13	10	MKS4G031503G00_	6	15	26.5	22.5	MKS4J031505B00_
0.22 "	6	12	13	10	MKS4G032203G00_	8	15	18	15	MKS4J032204F00_
	6	12.5	18	15	MKS4G032204C00_	6	15	26.5	22.5	MKS4J032205B00_
0.33 "	8	15	18	15	MKS4G033304F00_	7	16.5	26.5	22.5	MKS4J033305D00_
						9	19	31.5	27.5	MKS4J033306A00_
0.47 "	8	15	18	15	MKS4G034704F00_	10.5	19	26.5	22.5	MKS4J034705G00_
	6	15	26.5	22.5	MKS4G034705B00_	9	19	31.5	27.5	MKS4J034706A00_
0.68 "	7	16.5	26.5	22.5	MKS4G036805D00_	11	21	26.5	22.5	MKS4J036805I00_
						11	21	31.5	27.5	MKS4J036806B00_
1.0 μF	10.5	19	26.5	22.5	MKS4G041005G00_	11	21	31.5	27.5	MKS4J041006B00_
	11	21	31.5	27.5	MKS4G041006B00_					
1.5 "	11	21	26.5	22.5	MKS4G041505I00_	15	26	31.5	27.5	MKS4J041506F00_
	11	21	31.5	27.5	MKS4G041506B00_					
2.2 "	11	21	31.5	27.5	MKS4G042206B00_	17	34.5	31.5	27.5	MKS4J042206I00_
						15	26	41.5	37.5	MKS4J042207D00_
3.3 "	13	24	31.5	27.5	MKS4G043306D00_	20	39.5	31.5	27.5	MKS4J043306J00_
						19	32	41.5	37.5	MKS4J043307F00_
4.7 "	17	29	31.5	27.5	MKS4G044706G00_	20	39.5	41.5	37.5	MKS4J044707G00_
6.8 "	17	34.5	31.5	27.5	MKS4G046806I00_	24	45.5	41.5	37.5	MKS4J046807H00_
	15	26	41.5	37.5	MKS4G046807D00_					
10 μF	19	32	41.5	37.5	MKS4G051007F00_					
15 "	20	39.5	41.5	37.5	MKS4G051507G00_					

* AC voltage: $f = 50 \text{ Hz}$; $1.4 \times U_{\text{rms}} + \text{UDC} \leq U_r$

**PCM = Printed circuit module = lead spacing

* Admissible AC voltage 250 VAC max.

Dims. in mm.

Part number completion:

Tolerance: 20 % = M

10 % = K

5 % = J

Packing: bulk = S

Lead length: 6-2 = SD

Taped version see page 140.

Rights reserved to amend design data without prior notification.

Continuation page 61

Continuation

General Data

Capacitance	1000 VDC/400 VAC*					1500 VDC/400 VAC*				
	W	H	L	PCM**	Part number	W	H	L	PCM**	Part number
1000 pF	3	8.5	10	7.5	MKS4O111002B00_____	4	9	13	10	MKS4S011003C00_____
	4	9	13	10	MKS4O111003C00_____					
1500 "	3	8.5	10	7.5	MKS4O111502B00_____	4	9	13	10	MKS4S011503C00_____
	4	9	13	10	MKS4O111503C00_____					
2200 "	3	8.5	10	7.5	MKS4O112202B00_____	4	9	13	10	MKS4S012203C00_____
	4	9	13	10	MKS4O112203C00_____					
3300 "	4	9	10	7.5	MKS4O113302C00_____	4	9	13	10	MKS4S013303C00_____
	4	9	13	10	MKS4O113303C00_____					
4700 "	4	9	10	7.5	MKS4O114702C00_____	4	9	13	10	MKS4S014703C00_____
	4	9	13	10	MKS4O114703C00_____					
6800 "	4.5	9.5	10.3	7.5	MKS4O116802D00_____	5	11	13	10	MKS4S016803F00_____
	4	9	13	10	MKS4O116803C00_____					
0.01 µF	5	10.5	10.3	7.5	MKS4O121002E00_____	6	12	13	10	MKS4S021003G00_____
	5	11	13	10	MKS4O121003F00_____					
0.015 "	5.7	12.5	10.3	7.5	MKS4O121502F00_____	6	12.5	18	15	MKS4S021504C00_____
	6	12	13	10	MKS4O121503G00_____					
0.022 "	5	11	18	15	MKS4O122204B00_____	7	14	18	15	MKS4S022204D00_____
0.033 "	6	12.5	18	15	MKS4O123304C00_____	8	15	18	15	MKS4S023304F00_____
	6	15	26.5	22.5	MKS4O123305B00_____					
0.047 "	7	14	18	15	MKS4O124704D00_____	7	16.5	26.5	22.5	MKS4S024705D00_____
	6	15	26.5	22.5	MKS4O124705B00_____					
0.068 "	8	15	18	15	MKS4O126804F00_____	8.5	18.5	26.5	22.5	MKS4S026805F00_____
	6	15	26.5	22.5	MKS4O126805B00_____					
0.1 µF	9	16	18	15	MKS4O131004J00_____	10.5	19	26.5	22.5	MKS4S031005G00_____
	7	16.5	26.5	22.5	MKS4O131005D00_____					
0.15 "	8.5	18.5	26.5	22.5	MKS4O131505F00_____	11	21	31.5	27.5	MKS4S031506B00_____
0.22 "	10.5	19	26.5	22.5	MKS4O132205G00_____	13	24	31.5	27.5	MKS4S032206D00_____
0.33 "	11	21	26.5	22.5	MKS4O133305I00_____	17	34.5	31.5	27.5	MKS4S033306I00_____
	11	21	31.5	27.5	MKS4O133306B00_____					
0.47 "	13	24	31.5	27.5	MKS4O134706D00_____	20	39.5	31.5	27.5	MKS4S034706J00_____
0.68 "	15	26	31.5	27.5	MKS4O136806F00_____	20	39.5	41.5	37.5	MKS4S036807G00_____
1.0 µF	17	29	31.5	27.5	MKS4O141006G00_____	24	45.5	41.5	37.5	MKS4S041007H00_____
	17	29	41.5	37.5	MKS4O141007E00_____					
1.5 "	19	32	41.5	37.5	MKS4O141507F00_____					
2.2 "	20	39.5	41.5	37.5	MKS4O142207G00_____					
3.3 "	24	45.5	41.5	37.5	MKS4O143307H00_____					

* AC voltage: $f = 50 \text{ Hz}; 1.4 \times U_{\text{rms}} + U_{\text{DC}} \leq U_r$

** PCM = Printed circuit module = lead spacing

Dims. in mm.

Part number completion:

Tolerance: 20 % = M

10 % = K

5 % = J

Packing: bulk = S

Lead length: 6-2 = SD

Taped version see page 140.

Rights reserved to amend design data without prior notification.

Continuation page 62

Continuation

General Data

Capacitance	2000 VDC/400 VAC*				
	W	H	L	PCM**	Part number
1000 pF	4	9	13	10	MKS4U011003C00_
1500 "	4	9	13	10	MKS4U011503C00_
2200 "	5	11	13	10	MKS4U012203F00_
3300 "	6	12	13	10	MKS4U013303H00_
	5	11	18	15	MKS4U013304B00_
4700 "	5	11	18	15	MKS4U014704B00_
6800 "	6	12.5	18	15	MKS4U016804C00_
0.01 µF	7	14	18	15	MKS4U021004D00_
	6	15	26.5	22.5	MKS4U021005B00_
0.015 "	6	15	26.5	22.5	MKS4U021505B00_
0.022 "	7	16.5	26.5	22.5	MKS4U022205D00_
0.033 "	10.5	19	26.5	22.5	MKS4U023305G00_
0.047 "	11	21	26.5	22.5	MKS4U024705I00_
	11	21	31.5	27.5	MKS4U024706B00_
0.068 "	11	21	31.5	27.5	MKS4U026806B00_
0.1 µF	13	24	31.5	27.5	MKS4U031006D00_
0.15 "	17	29	31.5	27.5	MKS4U031506G00_
	13	24	41.5	37.5	MKS4U031507C00_
0.22 "	17	29	41.5	37.5	MKS4U032207E00_
0.33 "	20	39.5	41.5	37.5	MKS4U033307G00_
0.47 "	24	45.5	41.5	37.5	MKS4U034707H00_

The values of the WIMA MKS 4-LN range according to the main catalogue 2009 are still available on request.

Part number completion:

Tolerance: 20 % = M
10 % = K
5 % = J

Packing: bulk = S
Lead length: 6-2 = SD

Taped version see page 140.







* AC voltage: $f = 50 \text{ Hz}$; $1.4 \times U_{\text{rms}} + \text{UDC} \leq U_r$

** PCM = Printed circuit module = lead spacing

Dims. in mm.

Rights reserved to amend design data without prior notification.

Permissible AC voltage in relation to frequency at 10° C internal temperature rise (general guide).



Recommendation for Processing and Application of Through-Hole Capacitors

Soldering Process

A preheating of through-hole WIMA capacitors is allowed for temperatures $T_{\max} < 100^{\circ}\text{C}$.
In practice a preheating duration of $t < 5$ min. has been proven to be best.


Single wave soldering

Soldering bath temperature: $T < 260^{\circ}\text{C}$
Immersion time: $t < 5$ sec

Double wave soldering

Soldering bath temperature: $T < 260^{\circ}\text{C}$
Immersion time: $2 \times t < 3$ sec

Due to different soldering processes and heat requirements the graphs are to be regarded as a recommendation only.



WIMA Quality and Environmental Philosophy

ISO 9001:2000 Certification

ISO 9001:2000 is an international basic standard of quality assurance systems for all branches of industry. The approval according to ISO 9001:2000 of our factories by the VDE inspectorate certifies that organisation, equipment and monitoring of quality assurance in our factories correspond to internationally recognized standards.

WIMA WPCS

The WIMA Process Control System (WPCS) is a quality surveillance and optimization system developed by WIMA. WPCS is a major part of the quality-oriented WIMA production. Points of application of WPCS during production process:

- incoming material inspection
- metallization
- film inspection
- schoopage
- pre-healing
- lead attachment
- cast resin preparation/encapsulation
- 100% final inspection
- AQL check

WIMA Environmental Policy

All WIMA capacitors, irrespective of whether through-hole devices or SMD, are made of environmentally friendly materials. Neither during manufacture nor in the product itself any toxic substances are used, e.g.

- Lead
- PCB
- CFC
- Hydrocarbon chloride
- Chromium 6+
- PBB/PBDE
- Arsenic
- Cadmium
- Mercury
- etc.

We merely use pure, recyclable materials for packing our components, such as:

- carton
- cardboard
- adhesive tape made of paper
- polystyrene

We almost completely refrain from using packing materials such as:

- foamed polystyrene (Styropor®)
- adhesive tapes made of plastic
- metal clips

RoHS Compliance

According to the RoHS Directive 2002/95/EC certain hazardous substances like e.g. lead, cadmium, mercury must not be used any longer in electronic equipment as of July 1st, 2006. For the sake of the environment WIMA has refrained from using such substances since years already.



WIMA Kondensatoren sind bleifrei konform RoHS 2002/95/EG

WIMA capacitors are lead free in accordance with RoHS 2002/95/EC

Tape for lead-free WIMA capacitors

DIN EN ISO 14001:2005

WIMA's environmental management has been established in accordance with the guidelines of DIN EN ISO 14001:2005. The certification has been granted in June 2006.

Typical Dimensions for Taping Configuration




Diagram 2: PCM 10/15 mm

Diagram 3: PCM 22.5 and 27.5*mm

*PCM 27.5 tapping possible with two feed holes between components

Designation	Symbol	Dimensions for Radial Taping										
		PCM 2.5 tapping	PCM 5 tapping	PCM 7.5 tapping	PCM 10 tapping*	PCM 15 tapping*	PCM 22.5 tapping	PCM 27.5 tapping				
Carrier tape width	W	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5				
Hold-down tape width	W ₀	6.0 for hot-sealing adhesive tape	6.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape				
Hole position	W ₁	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5				
Hold-down tape position	W ₂	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.				
Feed hole diameter	D ₀	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2				
Pitch of component	P	12.7 ±1.0	12.7 ±1.0	12.7 ±1.0	25.4 ±1.0	25.4 ±1.0	38.1 ±1.5	38.1 ±1.5 or 50.8 ±1.5				
Feed hole pitch	P ₀	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch				
Feed hole centre to lead	P ₁	5.1 ±0.5	3.85 ±0.7	2.6 ±0.7	7.7 ±0.7	5.2 ±0.7	7.8 ±0.7	5.3 ±0.7				
Hole centre to component centre	P ₂	6.35 ±1.3	6.35 ±1.3	6.35 ±1.3	12.7 ±1.3	12.7 ±1.3	19.05 ±1.3	19.05 ±1.3				
Feed hole centre to bottom edge of the component	H	16.5 ±0.3 18.5 ±0.5	16.5 ±0.3 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5				
Feed hole centre to top edge of the component	H ₁	H+H _{component} < H ₁ 32.25 max.	H+H _{component} < H ₁ 32.25 max.	H+H _{component} < H ₁ 24.5 to 31.5	H+H _{component} < H ₁ 25.0 to 31.5	H+H _{component} < H ₁ 26.0 to 37.0	H+H _{component} < H ₁ 30.0 to 43.0	H+H _{component} < H ₁ 35.0 to 45.0				
Lead spacing at upper edge of carrier tape	F	2.5 ±0.5	5.0 ^{+0.8} _{-0.2}	7.5 ±0.8	10.0 ±0.8	15 ±0.8	22.5 ±0.8	27.5 ±0.8				
Lead diameter	d	0.4 ±0.05	0.5 ±0.05	0.5 ±0.05 or 0.6 ^{+0.06} _{-0.05}	0.5 ±0.05 or 0.6 ^{+0.06} _{-0.05}	0.8 ^{+0.08} _{-0.05}	0.8 ^{+0.08} _{-0.05}	0.8 ^{+0.08} _{-0.05}				
Component alignment	Δh	± 2.0 max.	± 2.0 max.	± 3.0 max.	± 3.0 max.	± 3.0 max.	± 3.0 max.	± 3.0 max.				
Total tape thickness	t	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2				
Package (see also page 141)		ROLL/AMMO			AMMO							
	REEL	∅ 360 max. ∅ 30 ±1	B 52 ±2 58 ±2	depending on comp. dimensions		REEL	∅ 360 max. ∅ 30 ±1	B 52 ±2 58 ±2 or 66 ±2	REEL	∅ 500 max. ∅ 25 ±1	B 60 ±2 68 ±2	depending on PCM and component dimensions
Unit		see details page 143.										

Dims in mm.

* Diameter of leads see General Data.

* PCM 10 and PCM 15 can be crimped to PCM 7.5.

Position of components according to PCM 7.5 (sketch 1). P₀ = 12.7 or 15.0 is possible

Please clarify customer-specific deviations with the manufacturer.



Packing Quantities for Bulk Capacitors and TPS*

PCM	Size			pcs. per packaging unit bulk			pcs. per packaging unit/TPS*	
	Part number codes	WV	H	L	Mini M	Standard S	Maxi G	Mini X
2.5 mm	2.5	7	4.6	1000	5000	10000	-	-
	3	7.5	4.6	1000	5000	10000	-	-
	3.8	8.5	4.6	1000	5000	10000	-	-
	4.6	9	4.6	1000	5000	10000	-	-
	5.5	10	4.6	1000	5000	10000	-	-
5 mm	2.5	6.5	7.2	2000	5000	10000	-	-
	3	7.5	7.2	1000	5000	-	-	-
	3.5	8.5	7.2	1000	5000	-	-	-
	4.5	6	7.2	1000	6000	-	-	-
	4.5	9.5	7.2	1000	4000	-	-	-
	5	10	7.2	1000	3500	-	-	-
	5.5	7	7.2	1000	4000	-	-	-
	5.5	11.5	7.2	500	2500	-	-	-
	6.5	8	7.2	1000	2500	-	-	-
	7.2	8.5	7.2	500	2500	-	-	-
	7.2	13	7.2	500	2000	-	-	-
	8.5	10	7.2	500	2000	-	-	-
	8.5	14	7.2	500	1500	-	-	-
11	16	7.2	250	1000	-	-	-	
7.5 mm	2.5	7	10	1000	5000	-	-	-
	3	8.5	10	1000	5000	-	-	-
	4	9	10	1000	4000	-	-	-
	4.5	9.5	10.3	1000	3500	-	-	-
	5	10.5	10.3	1000	3000	-	-	-
	5.7	12.5	10.3	500	2000	-	-	-
	7.2	12.5	10.3	500	1500	-	-	-
10 mm	3	9	13	1000	3000	-	-	-
	4	8.5	13.5	500	3000	-	-	-
	4	9	13	1000	3000	-	-	-
	4	9.5	13	1000	3000	-	-	-
	5	10	13.5	500	2000	-	-	-
	5	11	13	1000	3000	-	-	-
	6	12	13	800	2400	-	-	-
	6	12.5	13	800	2400	-	-	-
15 mm	8	12	13	500	2000	-	-	-
	5	11	18	800	2400	-	-	-
	5	13	19	200	1000	-	-	-
	6	12.5	18	500	2000	-	-	-
	6	14	19	250	1000	-	-	-
	7	14	18	400	1600	-	-	-
	7	15	19	250	1000	-	-	-
	8	15	18	400	1200	-	-	-
	8	17	19	100	500	-	-	-
	9	14	18	400	1200	-	-	-
	9	16	18	300	900	-	-	-
22.5 mm	10	18	19	100	500	-	-	-
	11	14	18	300	1000	-	-	-
	5	14	26.5	300	1200	-	-	-
	6	15	26.5	250	1000	-	-	-
	7	16.5	26.5	190	760	-	-	-
	8	20	28	-	-	-	115	690
	8.5	18.5	26.5	-	-	-	220	880
	10	22	28	-	-	-	90	540
	10.5	19	26.5	-	-	-	170	680
27.5 mm	10.5	20.5	26.5	-	-	-	170	680
	11	21	26.5	-	-	-	170	680
	12	24	28	-	-	-	75	450
	9	19	31.5	-	-	-	160	640
	11	21	31.5	-	-	-	136	544
	13	24	31.5	-	-	-	112	448
	13	25	33	-	-	-	56	336
	15	26	31.5	-	-	-	96	384
	15	26	33	-	-	-	48	288
	17	29	31.5	-	-	-	88	176
37.5 mm	17	34.5	31.5	-	-	-	88	176
	20	32	33	-	-	-	36	216
	20	39.5	31.5	-	-	-	36	144
	9	19	41.5	-	-	-	60	480
	11	22	41.5	-	-	-	51	408
	13	24	41.5	-	-	-	84	252
15	26	41.5	-	-	-	72	144	
17	29	41.5	-	-	-	66	132	
19	32	41.5	-	-	-	54	108	
20	39.5	41.5	-	-	-	27	108	
24	45.5	41.5	-	-	-	21	84	

Rights reserved to amend design data without prior notification.
Samples and pre-production needs on request.

■ Moulded versions.

* Tray-Packing-System

Packing Units for Taped Capacitors with Radial Leads



PCM	Size			ROLL		REEL				AMMO			
				H16.5	H18.5	ø 360		ø 500		340 x 340		490 x 370	
Part number codes	W	H	L	N	O	F	I	H	J	A	C	B	D
2.5 mm	2.5	7	4.6	2200		2500		-		2800		-	
	3	7.5	4.6	2000		2300		-		2300		-	
	3.8	8.5	4.6	1500		1800		-		1800		-	
	4.6	9	4.6	1200		1500		-		1500		-	
	5.5	10	4.6	900		1200		-		1200		-	
5 mm	2.5	6.5	7.2	2200		2500		-		2800		-	
	3	7.5	7.2	2000		2300		-		2300		-	
	3.5	8.5	7.2	1600		2000		-		2000		-	
	4.5	6	7.2	1300		1500		-		1500		-	
	4.5	9.5	7.2	1300		1500		-		1500		-	
	5	10	7.2	1100		1400		-		1400		-	
	5.5	7	7.2	1000		1200		-		1200		-	
	5.5	11.5	7.2	1000		1200		-		1200		-	
	6.5	8	7.2	800		1000		-		1000		-	
	7.2	8.5	7.2	700		1000		-		1000		-	
	7.2	13	7.2	700		950		-		1000		-	
	8.5	10	7.2	600		800		-		800		-	
	8.5	14	7.2	600		800		-		800		-	
11	16	7.2	500		700		-		700		-		
7.5 mm	2.5	7	10	-		2500		4400		2800		-	
	3	8.5	10	-		2200		4300		2300		4150	
	4	9	10	-		1700		3200		1700		3100	
	4.5	9.5	10.3	-		1500		2900		1400		2800	
	5	10.5	10.3	-		1300		2500		1300		-	
	5.7	12.5	10.3	-		1000		2200		1100		-	
	7.2	12.5	10.3	-		900		1800		1000		-	
10 mm	3	9	13	-		1100		2200		-		1900	
	4	8.5	13.5	-		900		1600		-		1450	
	4	9	13	-		900		1600		-		1450	
	4	9.5	13	-		900		1600		-		1400	
	5	10	13.5	-		700		1300		-		1200	
	5	11	13	-		700		1300		-		1200	
	6	12	13	-		550		1100		-		1000	
	6	12.5	13	-		550		1100		-		1000	
8	12	13	-		400		800		-		740		
15 mm	5	11	18	-		600		1200		-		1150	
	5	13	19	-		600		1200		-		1200	
	6	12.5	18	-		500		1000		-		1000	
	6	14	19	-		500		1000		-		1000	
	7	14	18	-		450		900		-		850	
	7	15	19	-		450		900		-		850	
	8	15	18	-		400		800		-		740	
	8	17	19	-		400		800		-		740	
	9	14	18	-		350		700		-		650	
	9	16	18	-		350		700		-		650	
	10	18	19	-		300		650		-		590	
11	14	18	-		300		600		-		540		
22.5 mm	5	14	26.5	-		-		800		-		770	
	6	15	26.5	-		-		700		-		640	
	7	16.5	26.5	-		-		600		-		550	
	8	20	28	-		-		500		-		480	
	8.5	18.5	26.5	-		-		480		-		450	
	10	22	28	-		-		420		-		380	
	10.5	19	26.5	-		-		400		-		360	
	10.5	20.5	26.5	-		-		400		-		360	
	11	21	26.5	-		-		380		-		350	
	12	24	28	-		-		350		-		310	
27.5 mm	9	19	31.5	-		-		460/340*		-		420	
	11	21	31.5	-		-		380/280*		-		350	
	13	24	31.5	-		-		300		-		290	
	15	26	31.5	-		-		270		-		250	

* for 2-inch transport pitches.

Samples and pre-production needs 1 packing unit minimum.

■ Moulded versions.

Rights reserved to amend design data without prior notification.



WIMA Part Number System

A WIMA part number consists of 18 digits and is composed as follows:

- Field 1 - 4: Type description
- Field 5 - 6: Rated voltage
- Field 7 - 10: Capacitance
- Field 11 - 12: Size and PCM
- Field 13 - 14: Special features (e.g. Snubber versions)
- Field 15: Capacitance tolerance
- Field 16: Packing
- Field 17 - 18: Lead length (untaped)

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
M	K	S	2	C	0	3	1	0	0	1	A	0	0	M	S	S	D
MKS 2				63 VDC		0.01 μ F			2.5x6.5x7.2		-		20%	bulk	6-2		

<p>Type description:</p> <p>SMD-PET = SMDT SMD-PEN = SMDN SMD-PPS = SMDI FKP 02 = FKS0 MKS 02 = MKS0 FKS 2 = FKS2 FKM 2 = FKM2 FKP 2 = FKP2 MKS 2 = MKS2 MKP 2 = MKP2 MKI 2 = MKI2 FKS 3 = FKS3 FKM 3 = FKM3 FKP 3 = FKP3 MKS 4 = MKS4 MKM 4 = MKM4 MKP 4 = MKP4 MKP 10 = MKP1 FKP 4 = FKP4 FKP 1 = FKP1 MKP-X2 = MKX2 MKP-X2 R = MKXR MKP-Y2 = MKY2 MP 3-X2 = MPX2 MP 3-X1 = MPX1 MP 3-Y2 = MPY2 MP 3R-Y2 = MPYR Snubber FKP = SNFP Snubber MKP = SNMP GTO MKP = GTOM DC-LINK MKP 4 = DCP4 DC-LINK MKP C = DCPC DC-LINK HC = DCH_ SuperCap C = SCSC SuperCap MC = SMC SuperCap R = SCSR SuperCap MR = SCMR</p>	<p>Rated voltage:</p> <p>16 VDC = A0 2.5 VDC = A1 4 VDC = A2 14 VDC = A3 28 VDC = A4 40 VDC = A5 50 VDC = B0 63 VDC = C0 100 VDC = D0 160 VDC = E0 250 VDC = F0 400 VDC = G0 630 VDC = J0 800 VDC = L0 850 VDC = M0 1000 VDC = O1 1200 VDC = Q0 1600 VDC = T0 2000 VDC = U0 2500 VDC = V0 4000 VDC = X0 6000 VDC = Y0 250 VAC = OVV 275 VAC = 1W 300 VAC = 2W 400 VAC = 3W 440 VAC = 4W 500 VAC = 5W ...</p>	<p>Capacitance:</p> <p>22 pF = 0022 47 pF = 0047 100 pF = 0100 220 pF = 0220 470 pF = 0470 1000 pF = 1100 2200 pF = 1220 4700 pF = 1470 0.01 μF = 2100 0.022 μF = 2220 0.047 μF = 2470 0.1 μF = 3100 0.22 μF = 3220 0.47 μF = 3470 1 μF = 4100 2.2 μF = 4220 4.7 μF = 4470 10 μF = 5100 22 μF = 5220 47 μF = 5470 100 μF = 6100 220 μF = 6220 1 F = A010 2.5 F = A025 50 F = A500 100 F = B100 600 F = B600 1200 F = C120 ...</p>	<p>Size:</p> <p>4.8x3.3x3 Size 1812 = X1 5.7x5.1x3.5 Size 2220 = Y1 7.2x6.1x3 Size 2824 = T1 2.5x7x4.6 PCM 2.5 = 0B 3x7.5x4.6 PCM 2.5 = 0C 2.5x6.5x7.2 PCM 5 = 1A 3x7.5x7.2 PCM 5 = 1B 2.5x7x10 PCM 7.5 = 2A 3x8.5x10 PCM 7.5 = 2B 3x9x13 PCM 10 = 3A 4x9x13 PCM 10 = 3B 5x11x18 PCM 15 = 4A 6x12.5x18 PCM 15 = 4B 5x14x26.5 PCM 22.5 = 5A 6x15x26.5 PCM 22.5 = 5B 9x19x31.5 PCM 27.5 = 6A 11x21x31.5 PCM 27.5 = 6B 9x19x41.5 PCM 37.5 = 7A 11x22x41.5 PCM 37.5 = 7B 94x49x182 DCH_ = H0 94x77x182 DCH_ = H1 ...</p>	<p>Special features:</p> <p>Standard = 00 Version A1 = 1A Version A1.1 = 1B ...</p>	<p>Tolerance:</p> <p>20% = M 10% = K 5% = J 2.5% = H 1% = E ...</p>	<p>Packing:</p> <p>AMMO H16.5 340x340 = A AMMO H16.5 490x370 = B AMMO H18.5 340x340 = C AMMO H18.5 490x370 = D REEL H16.5 360 = F REEL H16.5 500 = H REEL H18.5 360 = I REEL H18.5 500 = J ROLL H16.5 = N ROLL H18.5 = O BLISTER W12 180 = P BLISTER W12 330 = Q BLISTER W16 330 = R BLISTER W24 330 = T Bulk Mini = M Bulk Standard = S Bulk Maxi = G TPS Mini = X TPS Standard = Y ...</p>	<p>Lead length (untaped)</p> <p>3.5 \pm 0.5 = C9 6-2 = SD 16-1 = P4 ...</p>
--	---	--	--	---	---	--	--

The data on this page is not complete and serves only to explain the part number system. Part number information is listed on the pages of the respective WIMA range.